



Synerper Bands & Buckles

KB-KX Series

Synerper Bands



The Synerper Band & Synerper Buckles(KB & KX Series) use a base material 304 / 316 grade stainless steel for excellent resistance to temperature extremes, corrosion, weather, chemicals, salt sprays and UV radiation.

This Non-magnetic stainless steel Strapping(banding) can be flexibly used for any size hose, matching with buckle(clip) and fasten banding tool are used for insulation, mount traffic sign, commercial signs, holiday decorations and so on.

Band Width : 9.5mm(3/8"), 12.7mm(1/2"), 15.9mm(5/8"), 19mm(3/4")

Band Thickness : 0.4mm, 0.5mm, 0.6mm, 0.7mm

Length: 30Meter(100 ft) per roll

PART NUMBERING - SYNERPER BANDS

KB	-	127	07	F	-	A
(1)		(2)	(3)	(4)		(5)

(1) Series

KB = Synerper Bands

(2) Width (mm)

Example: 095 = 9.50mm

127 = 12.7mm

159 = 15.9mm

190 = 19.0mm

(3) Thickness (mm)

Example: 04 = 0.4mm

05 = 0.5mm

06 = 0.6mm

07 = 0.7mm

(4) Base Material

F = 304 Stainless Steel

S = 316 Stainless Steel

(5) Coated Material

Blank = no coated material

Y = Polyester

N = Nylon

A = Acrylic

P = PPA

PART NUMBERING - SYNERPER BUCKLES

KX	-	54	F	-	A
(1)		(2)	(3)		(4)

(1) Series
KX = Synerper Buckles

(2) Buckle Type

(3) Base Material
F = 304 Stainless Steel
S = 316 Stainless Steel

(4) Coated Material
Blank = no coated material
Y = Polyester
N = Nylon
A = Acrylic
P = PPA

Synerper Buckle Type



Part No	Strapping size	
	Inch	mm
KX-53	3/8	9.5
KX-54	1/2	12.7
KX-55	5/8	16
KX-56	3/4	19



Part No	Strapping size	
	Inch	mm
KX-33	3/8	9.5
KX-34	1/2	12.7
KX-35	5/8	16
KX-36	3/4	19

Tension Banding Tool

Durable Tensioner with cutter & hammer knob for binding irregular & non-compressible packages for stainless steel strapping.



Synerper Group Limited

(A member of Synerper Corp Limited)

Room 704, 7/F., Crown Industrial Building, 106 How Ming Street, Kwun Tong, Kowloon, Hong Kong

TEL: +852 3590 9060 FAX: +852 3590 9061 email: synerper@synerper.com www.synerper.com