

Waterproof Cable Gland (SCG Series) PG Thread

PRODUCT OVERVIEW:

Material: PA(Nylon)

Thread Type: PG

Hermetic Seal: NBR

O-Ring: EPDM

Material: Nylon

Working Temperature:


Static State: From -40°C to 100°C; Max Instantaneous Temperature Up to 120°C

Dynamic State: From -20°C to 80°C; Max Instantaneous Temperature Up to 100°C

Color: Grey, Black and Subject to Customer Requested

Fire Rating: UL 94-V2

Ingress Protection Rating: IP68 / IP69K



Part Number	Thread Ø D1 (mm)	Cable Ø (mm)	H (mm)	GL for Normal Type (mm)	W r e n c h Size (mm)	GL for Long Type (mm)
SCG-P0705-●■	PG 7	2.0 - 5.0	21	8	15	15
SCG-P0707-●■	PG 7	3.0 - 6.5	21	8	15	15
SCG-P0906-●■	PG 9	2.0 - 6.0	22	8	19	15
SCG-P0908-●■	PG 9	4.0 - 8.0	22	8	19	15
SCG-P1107-●■	PG 11	3.0 - 7.0	25	8	22	15
SCG-P1110-●■	PG 11	5.0 - 10.0	25	8	22	15
SCG-P13509-●■	PG 13.5	5.0 - 9.0	27	9	24	15
SCG-P13512-●■	PG 13.5	6.0 - 12.0	27	9	24	15
SCG-P1612-●■	PG 16	7.0 - 12.0	28	10	27	15
SCG-P1614-●■	PG 16	10.0 - 14.0	28	10	27	15
SCG-P2116-●■	PG 21	9.0 - 16.0	31	11	33	15
SCG-P2118-●■	PG 21	13.0 - 18.0	31	11	33	15
SCG-P2920-●■	PG 29	13.0 - 20.0	39	11	42	15
SCG-P2925-●■	PG 29	18.0 - 25.0	39	11	42	15
SCG-P3626-●■	PG 36	20.0 - 26.0	48	13	53	18
SCG-P3632-●■	PG 36	22.0 - 32.0	48	13	53	18
SCG-P4231-●■	PG 42	25.0 - 31.0	49	13	60	18
SCG-P4238-●■	PG 42	32.0 - 38.0	49	13	60	18
SCG-P4830-●■	PG 48	25.0 - 30.5	49	14	65	18
SCG-P4835-●■	PG 48	29.0 - 35.0	49	14	65	18
SCG-P4840-●■	PG 48	30.5 - 40.0	49	14	65	18
SCG-P4844-●■	PG 48	37.0 - 44.0	49	14	65	18

Note: ● - Empty means Black Color and "G" means Grey Color
 ■ - Empty means Normal Type GL and "L" means Long Type GL